



NEW PADS INDUSTRY CO., LTD.

TYPE DM-021-SPRAY-DB SPRAY LAMINATING MACHINE 噴膠貼合機

5>ADHESIVE

ONE COMPONENT SOLVENT BASE MOISTURE CURING POLYURETHANE ADHESIVE
AFTER SPRAY LAMINATING, KEE 10-24 HOURS FOR MOISTURE CURING, THEN THE LAMINATED GOODS CAN BE USED AND NO NEED EXTRA HEAT FOR CURING

6>SUITABLE MATERIAL FOR LAMINATING

WIDELY USED FOR MOST OF LAMINATING MATERIALS, ESPECIALLY FOR LINGERIE INDUSRY THAT ARE USING SOFT AND/OR ELASTIC OR NON STRETCH OR LIGHT/HEAVY FABRIC OR FIBERFIL TO FABRIC OR PU FOAM TO FABRIC

7>MACHINE SIZE

7 X 2 X 1.9 METERS (LXWXH)

8>MACHINE WEIGHT

ABOUT 3100 KGS



1ST MATERIAL UN-ROLL



2ND MATERIAL UN-ROLL



SPRAY BOOTH



RE-ROOLING UNIT

WE WELCOME YOUR INQUIRY

NEW PADS INDUSTRY CO., LTD.

6F, NO. 16, SECTION 1, SHING SHENG SOUTH ROAD, TAIPEI, TAIWAN

TEL : 886-2-23949410

FAX : 886-2-23910004

WEB : www.newpads.com.tw

E-MAIL : dm.npi@msa.hinet.net

